



MILBANK[®]
ENERGY AT WORK

U7021-RL-TG-KK-RGE



Catalog Number	U7021-RL-TG-KK-RGE	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Small Hub Open Triplex Ground Horn Bypass Rochester Gas And Electric	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572232938	Jaw Quantity	4 Terminal
Length (IN)	4.125	Bypass Type	Horn Bypass
Width (IN)	8	Number of Meter Positions	1 Position
Height (IN)	15.5	Equipment Ground	Triplex Ground
Brand Name	Milbank	Hub Opening	Small Hub Opening
Type	Ringless Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Special Features	Rochester Gas and Electric	Load Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.125L x 8W x 15.5H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead		
Terminal	Lay in		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.