



MILBANK[®]
ENERGY AT WORK

U8173-XL-PSEG-DES



Catalog Number	U8173-XL-PSEG-DES	Terminal	Lay in
Marketing Product Description	5 Terminal Ringless Small Closing Plate Horn Bypass 7-8 In Barrel Lock Ground With Bracket Provision 1 Way Hub Screw Add Inhibitor Public Service Electric And Gas New Jersey	Insulation	Glass Polyester
UPC	784572202580	Mounting	Surface Mount
Length (IN)	4.125	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	11	Jaw Quantity	5 Terminal
Height (IN)	15.5	Bypass Type	Horn Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	Bonded Neutral
Special Features	Public Service Electric and Gas New Jersey	Hub Opening	Small Closing Plate
Application	Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	600 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.125L x 11W x 15.5H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.