



MILBANK
ENERGY AT WORK

U9980-DL-TG-KK-AEP



| | | | |
|-------------------------------|---------------------------------------------------------------------------------|---------------------------|----------------------------------------------|
| Catalog Number | U9980-DL-TG-KK-AEP | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Marketing Product Description | 4 Terminal Ringless 2 In Hub Triplex Ground Horn Bypass American Electric Power | Jaw Quantity | 4 Terminal |
| UPC | 784572268203 | Bypass Type | Horn Bypass |
| Length (IN) | 4.125 | Number of Meter Positions | 1 Position |
| Width (IN) | 8 | Equipment Ground | Triplex Ground |
| Height (IN) | 15.5 | Hub Opening | 2 Inch Hub |
| Brand Name | Milbank | Line Side Wire Range | 6 AWG - 350 kcmil |
| Type | Ringless Meter Socket | Load Side Wire Range | 6 AWG - 350 kcmil |
| Special Features | American Electric Power | Number Of Receptacles | 0 |
| Application | Meter Socket | | |
| Standard | UL Listed;Type 3R | | |
| Voltage Rating | 600 Volts Alternating Current | | |
| Amperage Rating | 200 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 4.125L x 8W x 15.5H | | |
| Number Of Cutouts | 0 | | |
| Cutout Size | No Main Breaker | | |
| Cable Entry | Overhead | | |
| Terminal | Lay in | | |
| Insulation | Glass Polyester | | |
| Mounting | Surface Mount | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.