MILBANK ENERGYAT WORK

UQFPH-100

00	CICCUT DECARE BODIES DE CONTRACTOR DE C	
0		100
0		
0	PR	

Catalog Number	UQFPH-100
Marketing Product Description	Milbank 100 Ampere 2 Pole 240 Volt Plug-in 22k Ampere Interrupting Capacity
UPC	784572201484
Length (IN)	3.281
Width (IN)	3
Height (IN)	6.063
Weight (LB)	2.7
Brand Name	Milbank
Туре	Current Interrupting Device
Special Features	Plug On
Application	Metering Accessory
Standard	UL Listed
Standard Voltage Rating	UL Listed 240 Volts Alternating Current
Voltage Rating	240 Volts Alternating Current
Voltage Rating Current Rating	240 Volts Alternating Current 100 Ampere
Voltage Rating Current Rating Frequency Rating	240 Volts Alternating Current 100 Ampere 60 Hertz
Voltage Rating Current Rating Frequency Rating Number of Phases	240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase
Voltage RatingCurrent RatingFrequency RatingNumber of PhasesFrame	240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase F-Frame
Voltage Rating Current Rating Frequency Rating Number of Phases Frame Trip Type	240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase F-Frame Thermal Magnetic 22,000 Ampere Interrupting

Connection	Bus to Lug
Auxiliary Contacts	No Auxiliary Contacts
Material	Non Metallic
Operating Temperature	40 Degrees Celsius

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.