

U1255-X-KK-K3-BLG



Catalog Number	U1255-X-KK-K3-BLG
Marketing Product Description	4 Terminal Ringless Large Closing Plate Horn Bypass 5 Position Single Connector 4-600kcmil 7-8 In Barrel Lock Ground With Bracket Provision
UPC	784572241725
Length (IN)	5.125
Width (IN)	54.688
Height (IN)	16
Brand Name	Milbank
Туре	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
<u></u>	5.125L x 54.688W x 16H
Size	5.125L X 54.000VV X 10H
Size Number Of Cutouts	0
Number Of Cutouts	0

Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	5 Positions
Equipment Ground	Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Barrel Lock Provision	7/8 Inch Knockout and Angle Bracket For Barrel Lock Provision
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.