



MILBANK
ENERGY AT WORK



U1282-XL-PSEG-DES

Catalog Number	U1282-XL-PSEG-DES
Marketing Product Description	5 Terminal Small Closing Plate Horn Bypass 2 Position 7-8 In Barrel Lock Ground With Bracket Provision Public Services Electric And Gas New Jersey
UPC	784572203709
Length (IN)	4.5
Width (IN)	24.5
Height (IN)	14
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Public Service Electric and Gas New Jersey
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	100 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 24.5W x 14H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground

Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	2 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	2 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Barrel Lock Provision	7/8 Inch Knockout and Angle Bracket For Barrel Lock Provision
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.