



MILBANK
ENERGY AT WORK

U2161-XT



Catalog Number	U2161-XT	Mounting	Surface Mount
Marketing Product Description	13 Terminal Ringless 2 Large Closing Plates Test Switch Provision 24in-34in-12in Painted Steel Single Front Lift Off Screw Cover Hasp	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572134898	Jaw Quantity	13 Terminal
Length (IN)	12	Bypass Type	No Bypass
Width (IN)	24	Number of Meter Positions	1 Position
Height (IN)	34	Equipment Ground	Ground Lug
Brand Name	Milbank	Hub Opening	Twin Large Closing Plates
Type	Ringless Meter Socket	Line Side Wire Range	14 - 10 AWG
Application	Meter Socket	Load Side Wire Range	14 - 10 AWG
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	400 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	12L x 24W x 34H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.