

U7423-XL



Closi Med	rminal Ringless Small ing Plate Lever Bypass ium Duty
IIPC 7845	
7043	572141018
Length (IN) 4.844	4
Width (IN) 13	
Height (IN) 19	
Brand Name Milbs	ank
Type Ring	less Meter Socket
Application Mete	er Socket
Standard UL Li	isted;Type 3R
Voltage Rating 600 V	Volts Alternating Current
Amperage Rating 200	Continuous Ampere
Phase 3 Phase	ase
Frequency Rating 60 H	ertz
Size 4.844	4L x 13W x 19H
Number Of Cutouts 0	
Cutout Size No N	Main Breaker
Cable Entry Over	rhead or Underground
Terminal Lay i	n
Insulation Glass	s Polyester
Mounting Surfa	ace Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	7 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.