## MILBANK<sup>®</sup> ENERGYAT WORK

## AP2300-04



| Catalog Number                | AP2300-04                           |
|-------------------------------|-------------------------------------|
| Marketing Product Description | 4 Terminal Ring Type 1.25 In<br>Hub |
| UPC                           | 784572223349                        |
| Length (IN)                   | 2.25                                |
| Width (IN)                    | 6.625                               |
| Height (IN)                   | 7.125                               |
| Brand Name                    | Milbank                             |
| Туре                          | Ring Type Meter Socket              |
| Application                   | Meter Socket                        |
| Standard                      | Non UL Listed;Type 3R               |
| Voltage Rating                | 600 Volts Alternating Current       |
| Amperage Rating               | 100 Continuous Ampere               |
| Phase                         | 1 Phase                             |
| Frequency Rating              | 60 Hertz                            |
| Size                          | 2.25L x 6.625W x 7.125H             |
| Number Of Cutouts             | 0                                   |
| Cutout Size                   | No Main Breaker                     |
| Cable Entry                   | Overhead                            |
| Terminal                      | Single Mechanical                   |
| Insulation                    | Glass Polyester                     |
| Mounting                      | Surface Mount                       |
| Enclosure                     | Aluminum with Powder Coat<br>Finish |

| Jaw Quantity              | 4 Terminal     |
|---------------------------|----------------|
| Bypass Type               | No Bypass      |
| Number of Meter Positions | 1 Position     |
| Equipment Ground          | Triplex Ground |
| Hub Opening               | 1 1/4 Inch Hub |
| Line Side Wire Range      | 12 - 1 AWG     |
| Load Side Wire Range      | 12 - 1 AWG     |
| Number Of Receptacles     | 0              |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.