



**MILBANK**  
ENERGY AT WORK

## S4244-X



Catalog Number	S4244-X	Mounting	Surface Mount
Marketing Product Description	13 Terminal Ringless Large Closing Plate Test Switch Provision 20in-34in-12in Painted Steel Single Front Lift Off Cover Hasp Current Transformer Rack Installed	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572286320	Jaw Quantity	13 Terminal
Length (IN)	20	Bypass Type	No Bypass
Width (IN)	12	Number of Meter Positions	1 Position
Height (IN)	34	Equipment Ground	Ground Lug
Brand Name	Milbank	Hub Opening	Large Closing Plate
Type	Ringless Meter Socket	Line Side Wire Range	14 - 10 AWG
Application	Meter Socket	Load Side Wire Range	14 - 10 AWG
Standard	Non UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	400 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	20L x 12W x 34H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	1/2 Inch Stud Line Side		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.