

U3765-XL



Clo	Ferminal Ring Type Small osing Plate Lever Bypass 5
	sition
JPC 784	4572138919
Length (IN) 4.5	5
Width (IN) 49.	.813
Height (IN) 16	
Brand Name Mil	lbank
Гуре Rin	ngless Meter Socket
Application Me	eter Socket
Standard UL	Listed;Type 3R
/oltage Rating 300	0 Volts Alternating Current
Amperage Rating 125	5 Continuous Ampere
Phase 1 F	Phase
Frequency Rating 60	Hertz
Size 4.5	5L x 49.813W x 16H
Number Of Cutouts 0	
Cutout Size No.	Main Breaker
Cable Entry Ov	verhead or Underground
Terminal Lay	y in
nsulation Gla	ass Polyester
Mounting Sui	rface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	5 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	Bypass 6 AWG - 350 kcmil, Non-Bypass 6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.