MILBANK ENERGYAT WORK

U2601-XL



Catalog Number	U2601-XL
Marketing Product Description	4 Terminal Ringless Small Closing Plate 2 Position 200 Ampere
UPC	784572135536
Length (IN)	4.5
Width (IN)	20.313
Height (IN)	16
Brand Name	Milbank
Туре	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 20.313W x 16H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground with End Wireway
Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	2 Positions
Equipment Ground	2 Barrel Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	2 AWG - 350 kcmil
Load Side Wire Range	Left Socket 6 AWG - 350 kcmil Right Socket 6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.