

## U3986-XL-100-LIS



Catalog Number	U3986-XL-100-LIS
Marketing Product Description	5 Terminal Ringless Large Hub Open Adapt To Small Hub Open Lever Bypass 1-100 Ampere Main Breaker Long Island Lighting Company
UPC	784572139275
Length (IN)	4.875
Width (IN)	13
Height (IN)	34
Brand Name	Milbank
Туре	Ringless Meter Socket
Special Features	Long Island Lighting Company
Application	Meter Socket With Main
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	100 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.875L x 13W x 34H
Number Of Cutouts	1
Cutout Size	One 100 Ampere Main Breaker
Cable Entry	Overhead or Underground

InsulationGlass PolyesterMountingSurface MountEnclosureG90 Galvanized Steel with Powder Coat FinishJaw Quantity5 TerminalBypass TypeLever BypassNumber of Meter Positions1 PositionEquipment Ground3 Barrel Ground LugHub OpeningSmall Closing PlateLine Side Wire Range2 AWG - 350 kcmilLoad Side Wire Range1 - 3 AWGNumber Of Receptacles0	Terminal	Lay in
Enclosure  G90 Galvanized Steel with Powder Coat Finish  Jaw Quantity  5 Terminal  Bypass Type  Lever Bypass  Number of Meter Positions  1 Position  Equipment Ground  3 Barrel Ground Lug  Hub Opening  Small Closing Plate  Line Side Wire Range  2 AWG - 350 kcmil  Load Side Wire Range  1 - 3 AWG	Insulation	Glass Polyester
Powder Coat Finish  Jaw Quantity 5 Terminal  Bypass Type Lever Bypass  Number of Meter Positions 1 Position  Equipment Ground 3 Barrel Ground Lug  Hub Opening Small Closing Plate  Line Side Wire Range 2 AWG - 350 kcmil  Load Side Wire Range 1 - 3 AWG	Mounting	Surface Mount
Bypass Type Lever Bypass  Number of Meter Positions 1 Position  Equipment Ground 3 Barrel Ground Lug  Hub Opening Small Closing Plate  Line Side Wire Range 2 AWG - 350 kcmil  Load Side Wire Range 1 - 3 AWG	Enclosure	
Number of Meter Positions 1 Position  Equipment Ground 3 Barrel Ground Lug  Hub Opening Small Closing Plate  Line Side Wire Range 2 AWG - 350 kcmil  Load Side Wire Range 1 - 3 AWG	Jaw Quantity	5 Terminal
Equipment Ground 3 Barrel Ground Lug Hub Opening Small Closing Plate Line Side Wire Range 2 AWG - 350 kcmil Load Side Wire Range 1 - 3 AWG	Bypass Type	Lever Bypass
Hub Opening Small Closing Plate  Line Side Wire Range 2 AWG - 350 kcmil  Load Side Wire Range 1 - 3 AWG	Number of Meter Positions	1 Position
Line Side Wire Range 2 AWG - 350 kcmil  Load Side Wire Range 1 - 3 AWG	Equipment Ground	3 Barrel Ground Lug
Load Side Wire Range 1 - 3 AWG	Hub Opening	Small Closing Plate
	Line Side Wire Range	2 AWG - 350 kcmil
Number Of Receptacles 0	Load Side Wire Range	1 - 3 AWG
	Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.