



MILBANK
ENERGY AT WORK

M400-APS



Catalog Number	M400-APS	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ring Type Small Hub Open 1-200 Ampere Main Breaker 4 Branch Circuit	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572116207	Jaw Quantity	4 Terminal
Length (IN)	5.938	Bypass Type	No Bypass
Width (IN)	9.375	Number of Meter Positions	1 Position
Height (IN)	47	Equipment Ground	3 Barrel Ground Lug
Brand Name	Milbank	Hub Opening	Small Hub Opening
Type	Ring Type Meter Socket	Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Application	Meter Socket With Main	Load Side Wire Range	1 AWG - 300 kcmil
Standard	UL Listed;Type 3R	Number Branch Circuits	1
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	320 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.938L x 9.375W x 47H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.