



MILBANK
ENERGY AT WORK

U227MTB/22



Catalog Number	U227MTB/22	Insulation	Fiberglass with Resin
Marketing Product Description	7 Terminal Ring Type Small Closing Plate Link Bypass 1-200 Ampere Main Breaker 22k Ampere Interrupting Capacity Rating	Mounting	Surface Mount
UPC	784572232662	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	6	Jaw Quantity	7 Terminal
Width (IN)	22.125	Bypass Type	Link Bypass
Height (IN)	30	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	Ground Lug
Type	Ring Type Meter Socket	Hub Opening	Small Closing Plate
Application	Meter Socket With Main	Line Side Wire Range	6 AWG - 250 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 250 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	6L x 22.125W x 30H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Single Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.