



**MILBANK**  
ENERGY AT WORK

## U4322-O-BL



Catalog Number	U4322-O-BL	Mounting	Pedestal
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass 9-16 In Barrel Lock With Bracket Provision Single Pedestal Direct Bury	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572259829	Jaw Quantity	4 Terminal
Length (IN)	9.625	Bypass Type	Lever Bypass
Width (IN)	9.875	Number of Meter Positions	1 Position
Height (IN)	55	Equipment Ground	4 Barrel Ground Lug
Brand Name	Milbank	Hub Opening	Plain Top
Type	Ringless Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket With Main And Load Center	Number Branch Circuits	3
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	9.625L x 9.875W x 55H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Underground		
Terminal	Double Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.