MILBANK[®] ENERGYAT WORK

U5200-XL-41-L



Catalog Number	U5200-XL-41-L
Marketing Product Description	Unmetered Small Closing Plate 520GR TT30 Light Kit Single Pedestal Direct Bury
UPC	784572258242
Length (IN)	5.188
Width (IN)	8.7
Height (IN)	64.5
Brand Name	Milbank
Туре	Unmetered Power Supply
Special Features	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker
Application	RV Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.188L x 8.7W x 64.5H
Number Of Cutouts	2
Cutout Size	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker
Cable Entry	Underground

Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	0 Terminals
Bypass Type	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	2 Barrel Ground Lug and Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	4
Number Of Receptacles	2
Receptacle Configuration	One NEMA TT30 and One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.