



MILBANK
ENERGY AT WORK

UQFB-200



| | |
|-------------------------------|---|
| Catalog Number | UQFB-200 |
| Marketing Product Description | Milbank 200 Ampere 2 Pole 240 Volt Bolt-on 10k Ampere Interrupting Capacity |
| UPC | 784572146419 |
| Length (IN) | 3.281 |
| Width (IN) | 3 |
| Height (IN) | 7.438 |
| Weight (LB) | 3 |
| Brand Name | Milbank |
| Type | Current Interrupting Device |
| Special Features | Bolt On |
| Application | Metering Accessory |
| Standard | UL Listed |
| Voltage Rating | 240 Volts Alternating Current |
| Current Rating | 200 Ampere |
| Frequency Rating | 60 Hertz |
| Number of Phases | 1 Phase |
| Frame | F-Frame |
| Trip Type | Thermal Magnetic |
| Interrupt Rating | 10,000 Ampere Interrupting Capacity |
| Number Of Poles | 2 |
| Actuator | Lever |

| | |
|-----------------------|-----------------------|
| Connection | Lug to Lug |
| Auxiliary Contacts | No Auxiliary Contacts |
| Material | Non Metallic |
| Operating Temperature | 40 Degrees Celsius |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.