




U5091-RL-76GBGR



Catalog Number	U5091-RL-76GBGR
Marketing Product Description	4 Terminal Ringless Small Hub Open Lever Bypass 520GR 520GR 1450GB Surface Mount
UPC	784572292574
Length (IN)	4.844
Width (IN)	10
Height (IN)	34
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker
Application	Temporary Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.844L x 10W x 34H
Number Of Cutouts	3

Cutout Size	Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker
Cable Entry	Overhead
Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	Ground Bar
Hub Opening	Small Hub Opening
Number Branch Circuits	2
Number Of Receptacles	3
Receptacle Configuration	One NEMA 14-50 and Two NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.