




MILBANK
ENERGY AT WORK

U8667-O-2/200



Catalog Number	U8667-O-2/200	Mounting	Pedestal
Marketing Product Description	4 Terminal Ring Type Plain Top Double Pedestal 2-200 Ampere Main Breaker	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572291638	Jaw Quantity	4 Terminal
Length (IN)	12.593	Bypass Type	No Bypass
Width (IN)	12	Number of Meter Positions	2 Positions
Height (IN)	52	Equipment Ground	Quadplex Ground
Brand Name	Milbank	Hub Opening	Plain Top
Type	Ring Type Meter Socket	Load Side Wire Range	1 AWG - 300 kcmil
Application	Meter Socket With Main	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	12.593L x 12W x 52H		
Number Of Cutouts	2		
Cutout Size	Two 200 Ampere Main Breakers		
Cable Entry	Underground		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.