



MILBANK
ENERGY AT WORK

U4667-XT-9505



| | |
|-------------------------------|--|
| Catalog Number | U4667-XT-9505 |
| Marketing Product Description | 7 Terminal Bolt-in 2 Large Closing Plates Link Bypass Configuration 9505 |
| UPC | 784572246737 |
| Length (IN) | 6 |
| Width (IN) | 20.25 |
| Height (IN) | 43 |
| Brand Name | Milbank |
| Type | Bolt On Meter Socket |
| Application | Meter Socket |
| Standard | UL Listed;Type 3R |
| Voltage Rating | 600 Volts Alternating Current |
| Amperage Rating | 480 Continuous Ampere |
| Phase | 3 Phase |
| Frequency Rating | 60 Hertz |
| Size | 6L x 20.25W x 43H |
| Number Of Cutouts | 0 |
| Cutout Size | No Main Breaker |
| Cable Entry | Overhead or Underground |
| Terminal | 1/2 Inch Stud Line Side |
| Insulation | Glass Polyester |
| Mounting | Surface Mount |

| | |
|---------------------------|--|
| Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Jaw Quantity | 7 Terminal |
| Bypass Type | Link Bypass |
| Number of Meter Positions | 1 Position |
| Equipment Ground | 2 Barrel Ground Lug |
| Hub Opening | Twin Large Closing Plates |
| Number Of Receptacles | 0 |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.