



MILBANK
ENERGY AT WORK

U4908-O-55GBGR



Catalog Number	U4908-O-55GBGR	Cable Entry	Underground
Marketing Product Description	4 Terminal Ringless Plain Top 1450GB 520GR Surface Mount	Terminal	Lay in
UPC	784572273641	Insulation	Glass Polyester
Length (IN)	5.188	Mounting	Surface Mount
Width (IN)	9	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Height (IN)	25.938	Jaw Quantity	4 Terminal
Brand Name	Milbank	Bypass Type	No Bypass
Type	Ringless Meter Socket	Number of Meter Positions	Single Power Head
Special Features	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Ground Fault Breaker	Equipment Ground	2 Barrel Ground Lug
Application	Temporary Power	Hub Opening	Small Closing Plate
Standard	UL Listed;Type 3R	Number Branch Circuits	3
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	2
Amperage Rating	125 Continuous Ampere	Receptacle Configuration	One NEMA 14-50 and One NEMA 5-20 Ground Fault
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.188L x 9W x 25.938H		
Number Of Cutouts	2		
Cutout Size	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Ground Fault Breaker		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.