




MILBANK
ENERGY AT WORK



U2735-XT-K8

Catalog Number	U2735-XT-K8	Mounting	Surface Mount
Marketing Product Description	7 Terminal Ringless 2 Large Closing Plates Lever Bypass 5 Position Double Connector 4-600kcmil	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572320956	Jaw Quantity	7 Terminal
Length (IN)	6	Bypass Type	Lever Bypass
Width (IN)	62.313	Number of Meter Positions	5 Positions
Height (IN)	25.25	Equipment Ground	Ground Lug
Brand Name	Milbank	Hub Opening	Twin Large Closing Plates
Type	Ringless Meter Socket	Line Side Wire Range	Two 2 AWG - 600 kcmil
Application	Meter Socket	Load Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	6L x 62.313W x 25.25H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground with Center Wireway		
Terminal	Double Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.