



**MILBANK**  
ENERGY AT WORK

## UQFBH-M-100



Catalog Number	UQFBH-M-100	Actuator	Lever
Marketing Product Description	Milbank 100 Ampere 2 Pole 240 Volt Bolt-on 22k Ampere Interrupting Capacity Threaded Tang Load Side	Connection	Lug to Lug
UPC	784572302600	Auxiliary Contacts	No Auxiliary Contacts
Length (IN)	3.281	Material	Non Metallic
Width (IN)	3	Operating Temperature	40 Degrees Celsius
Height (IN)	7.438		
Weight (LB)	4		
Brand Name	Milbank		
Type	Current Interrupting Device		
Special Features	Load Side Threaded Tap Tangs		
Application	Metering Accessory		
Standard	UL Listed		
Voltage Rating	240 Volts Alternating Current		
Current Rating	100 Ampere		
Frequency Rating	60 Hertz		
Number of Phases	1 Phase		
Frame	F-Frame		
Trip Type	Thermal Magnetic		
Interrupt Rating	22,000 Ampere Interrupting Capacity		
Number Of Poles	2		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.