



MILBANK[®]
ENERGY AT WORK

U1256-X-QG-KK-K4



Catalog Number	U1256-X-QG-KK-K4	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Large Closing Plate Quadplex Ground Horn Bypass 6 Position Double Connector 2-600kcmil	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572191648	Jaw Quantity	4 Terminal
Length (IN)	5.125	Bypass Type	Horn Bypass
Width (IN)	62.875	Number of Meter Positions	6 Positions
Height (IN)	18	Equipment Ground	Quadplex Ground
Brand Name	Milbank	Hub Opening	Large Closing Plate
Type	Ringless Meter Socket	Load Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	300 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.125L x 62.875W x 18H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Double Mechanical		
Insulation	No Insulation		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.