



MPRV-100-20GR-78



Catalog Number	MPRV-100-20GR-78
Marketing Product Description	4 Terminal Ring Type Plain Top 1-100 Ampere Main Breaker 520GR Single Pedestal Direct Bury
UPC	784572279452
Length (IN)	4.01
Width (IN)	8.16
Height (IN)	78
Brand Name	Milbank
Type	Ring Type Meter Socket
Special Features	Single Pole 20 Ampere Breaker
Application	Mobile Home Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	100 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.01L x 8.16W x 78H
Number Of Cutouts	2
Cutout Size	One 100 Ampere Main Breaker and One Single Pole 20 Ampere Breaker
Cable Entry	Underground

Terminal	Double Mechanical
Insulation	Fiberglass with Resin
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Bar
Hub Opening	Plain Top
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Number Branch Circuits	4
Number Of Receptacles	1
Receptacle Configuration	One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.