

U5200-XL-552GR



Catalog Number	U5200-XL-552GR
Marketing Product Description	Unmetered Small Closing Plate 1450 1450 520GR Single Pedestal Direct Bury
UPC	784572317314
Length (IN)	5.188
Width (IN)	8.688
Height (IN)	64.5
Brand Name	Milbank
Туре	Unmetered Power Supply
Special Features	One Single Pole 20 Ampere Breaker and Two Double Pole 50 Ampere Breaker
Application	RV Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating
	Current
Amperage Rating	Current 125 Continuous Ampere
Amperage Rating Phase	
	125 Continuous Ampere
Phase	125 Continuous Ampere 1 Phase
Phase Frequency Rating	125 Continuous Ampere 1 Phase 60 Hertz
Phase Frequency Rating Size	125 Continuous Ampere 1 Phase 60 Hertz 5.188L x 8.688W x 64.5H

Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	0 Terminals
Bypass Type	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	2 Barrel Ground Lug and Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	1
Number Of Receptacles	3
Receptacle Configuration	Two NEMA 14-50 and One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.