



MILBANK
ENERGY AT WORK

CP3B1113JA50



Catalog Number	CP3B1113JA50	Mounting	Pad Mount
Marketing Product Description	Ring Type 100 Amperes 240 Volt 4 Terminal T-fuse Main 50k Mint Green	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572312395	Jaw Quantity	4 Terminal
Length (IN)	17	Bypass Type	Link Bypass
Width (IN)	16	Number of Meter Positions	1 Position
Height (IN)	48	Equipment Ground	Ground Bar
Brand Name	Milbank	Hub Opening	No Hub Opening
Type	Ring Type Metered Commercial Pedestal	Line Side Wire Range	6 AWG - 350 kcmil
Application	Power Distribution	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	120/240 Volts Alternating Current		
Amperage Rating	100 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	17L x 16W x 48H		
Number Of Cutouts	1		
Cutout Size	One 100 Ampere Main Fuse Pull Out Switch		
Cable Entry	Underground		
Terminal	Single Mechanical		
Insulation	No Insulation		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.