



MILBANK
ENERGY AT WORK

U5136-O-75-FMG



Catalog Number	U5136-O-75-FMG	Terminal	Double Mechanical
Marketing Product Description	4 Terminal Ringless Plain Top 1-Main Breaker Provision 1450 TT30 520GR Single Pedestal Direct Bury Florida Meter Group	Insulation	Glass Polyester
UPC	784572320611	Mounting	Pedestal
Length (IN)	10.25	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	9.688	Jaw Quantity	4 Terminal
Height (IN)	80	Bypass Type	Horn Bypass
Brand Name	Milbank	Number of Meter Positions	Single Power Head
Type	Ringless Meter Socket	Equipment Ground	Ground Bar
Application	Mobile Home Power	Hub Opening	Plain Top
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Branch Circuits	0
Amperage Rating	200 Continuous Ampere	Number Of Receptacles	3
Phase	1 Phase	Receptacle Configuration	One NEMA 14-50 and One NEMA TT30 and One NEMA 5-20 Ground Fault
Frequency Rating	60 Hertz		
Size	10.25L x 9.688W x 80H		
Number Of Cutouts	3		
Cutout Size	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker and One Double Pole 50 Ampere Breaker		
Cable Entry	Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.