



MILBANK
ENERGY AT WORK

U3000-O-2/K3L-BL



| | | | |
|-------------------------------|---|---------------------------|--|
| Catalog Number | U3000-O-2/K3L-BL | Mounting | Surface Mount |
| Marketing Product Description | 4 Terminal Ringless Plain Top Lever Bypass 2 Single Connector Locking 4-600kcmil 9-16 In Barrel Lock With Bracket Provision | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| UPC | 784572318403 | Jaw Quantity | 4 Terminal |
| Length (IN) | 4.844 | Bypass Type | Lever Bypass |
| Width (IN) | 15 | Number of Meter Positions | 1 Position |
| Height (IN) | 30 | Equipment Ground | 3 Barrel Ground Lug |
| Brand Name | Milbank | Hub Opening | Plain Top |
| Type | Ringless Meter Socket | Line Side Wire Range | 4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil |
| Application | Meter Socket | Load Side Wire Range | 4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil |
| Standard | UL Listed;Type 3R | Barrel Lock Provision | 9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision |
| Voltage Rating | 600 Volts Alternating Current | Number Of Receptacles | 0 |
| Amperage Rating | 320 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 4.844L x 15W x 30H | | |
| Number Of Cutouts | 0 | | |
| Cutout Size | No Main Breaker | | |
| Cable Entry | Underground | | |
| Terminal | Single Mechanical | | |
| Insulation | Glass Polyester | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.