



MILBANK
ENERGY AT WORK

MPRV-50-78



Catalog Number	MPRV-50-78	Insulation	Fiberglass with Resin
Marketing Product Description	4 Terminal Ring Type Plain Top 1450 Single Pedestal Direct Bury	Mounting	Pedestal
UPC	784572320192	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	4	Jaw Quantity	4 Terminal
Width (IN)	8.156	Bypass Type	No Bypass
Height (IN)	78	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	Ground Bar
Type	Ring Type Meter Socket	Hub Opening	Plain Top
Special Features	One Double Pole 50 Ampere Breaker	Line Side Wire Range	6 AWG - 350 kcmil
Application	Mobile Home Power	Load Side Wire Range	6 - 2/0 AWG
Standard	UL Listed;Type 3R	Number Branch Circuits	5
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	100 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4L x 8.156W x 78H		
Number Of Cutouts	1		
Cutout Size	One Double Pole 50 Ampere Breaker		
Cable Entry	Underground		
Terminal	Double Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.