



MILBANK[®]
ENERGY AT WORK

U3989-XL-100



Catalog Number	U3989-XL-100	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Small Closing Plate 1-100 Ampere Main Breaker 2 Branch Circuit	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572320765	Jaw Quantity	4 Terminal
Length (IN)	3.75	Bypass Type	No Bypass
Width (IN)	11	Number of Meter Positions	1 Position
Height (IN)	22	Equipment Ground	3 Barrel Ground Lug
Brand Name	Milbank	Hub Opening	Small Hub Opening
Type	Ringless Meter Socket	Line Side Wire Range	6 - 2/0 AWG
Application	Meter Socket With Main	Load Side Wire Range	4 - 1/0 AWG
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	100 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	3.75L x 11W x 22H		
Number Of Cutouts	1		
Cutout Size	One 100 Ampere Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Lay in		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.