

U7040-RL-KK-DPL



Catalog NumberU7040-RL-KK-DPLMarketing Product Descriptionareminal Ringless Small Hub spen Horn Bypass Delmarva over And LightLPC84572371088Length (IN)4.125Width (IN)11Height (IN)14.563Brand NameMilbankTypeMilbankApplicationMeter SocketStandardUL Listed;Type 3RYoltage Rating600 Volts Alternating CurrentPhase101Frequency Rating001 Volts Alternating CurrentSize1.25L x 111W x 14.563HNumber Of Cutouts0Gutout SizeNo Main BreakerCable EntryJorentead CurrentInsulationGiass PolyesterMountingSurface Mount		
Open Horn Bypass Delmarva Power And LightUPC784572371088Length (IN)4.125Width (IN)11Height (IN)14.563Brand NameMilbankTypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating600 Continuous AmperePhase1 PhaseSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Catalog Number	U7040-RL-KK-DPL
Length (IN)4.125Width (IN)11Height (IN)14.563Brand NameMilbankTypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Marketing Product Description	Open Horn Bypass Delmarva
Number of FunctionWidth (IN)11Height (IN)14.563Brand NameMilbankTypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	UPC	784572371088
Height (IN)14.563Brand NameMilbankTypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Length (IN)	4.125
Rind yameMilbankTypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Width (IN)	11
TypeRingless Meter SocketApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Height (IN)	14.563
ApplicationMeter SocketStandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundInsulationGlass Polyester	Brand Name	Milbank
StandardUL Listed;Type 3RVoltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Туре	Ringless Meter Socket
Voltage Rating600 Volts Alternating CurrentAmperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Application	Meter Socket
Amperage Rating200 Continuous AmperePhase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Standard	UL Listed;Type 3R
Phase1 PhaseFrequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Voltage Rating	600 Volts Alternating Current
Frequency Rating60 HertzSize4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Amperage Rating	200 Continuous Ampere
Size4.125L x 11W x 14.563HNumber Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Phase	1 Phase
Number Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Frequency Rating	60 Hertz
Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Size	4.125L x 11W x 14.563H
Cable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Number Of Cutouts	0
Terminal Lay in Insulation Glass Polyester	Cutout Size	No Main Breaker
Insulation Glass Polyester	Cable Entry	Overhead or Underground
	Terminal	Lay in
Mounting Surface Mount	Insulation	Glass Polyester
	Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	1 Position
Equipment Ground	Triplex Ground
Hub Opening	Small Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.