



MILBANK
ENERGY AT WORK

U5701-O-200S



Catalog Number	U5701-O-200S	Mounting	Pedestal
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass 1-200 Ampere Main Breaker Single Pedestal Direct Bury	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572474246	Jaw Quantity	4 Terminal
Length (IN)	10.27	Bypass Type	Lever Bypass
Width (IN)	9.875	Number of Meter Positions	Single Power Head
Height (IN)	80	Equipment Ground	Ground Bar
Brand Name	Milbank	Hub Opening	Plain Top
Type	Ringless Meter Socket	Number Branch Circuits	4
Application	Mobile Home Power	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	10.27L x 9.875W x 80H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Underground		
Terminal	Double Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.