



MILBANK
ENERGY AT WORK

U5330-O-55



Catalog Number	U5330-O-55	Terminal	Double Mechanical
Marketing Product Description	4 Terminal Ring Type Plain Top 1450 520GR Double Pedestal Pad Mount	Insulation	Glass Polyester
UPC	784572475007	Mounting	Pedestal
Length (IN)	11.313	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	8.656	Jaw Quantity	4 Terminal
Height (IN)	46.25	Bypass Type	No Bypass
Brand Name	Milbank	Number of Meter Positions	Double Power Head
Type	Ring Type Meter Socket	Equipment Ground	2 Barrel Ground Lug and Ground Bar
Special Features	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Breaker	Hub Opening	Plain Top
Application	RV Power	Line Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Number Branch Circuits	6
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	4
Amperage Rating	125 Continuous Ampere	Receptacle Configuration	Two NEMA 14-50 and Two NEMA 5-20 Ground Fault
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	11.313L x 8.656W x 46.25H		
Number Of Cutouts	4		
Cutout Size	Two Single Pole 20 Ampere Breakers and Two Double Pole 50 Ampere Breakers		
Cable Entry	Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.