



MILBANK
ENERGY AT WORK

U5169-XTL-200-EDE



Catalog Number	U5169-XTL-200-EDE	Terminal	Lay in
Marketing Product Description	4 Terminal Ring Type 2 Small Closing Plates 1-100 Ampere Main Breaker 8 Branch Circuit Empire District Electric	Insulation	Glass Polyester
UPC	784572478558	Mounting	Surface Mount
Length (IN)	4.5	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	14.125	Jaw Quantity	4 Terminal
Height (IN)	30	Bypass Type	No Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ring Type Meter Socket	Equipment Ground	Ground Bar
Special Features	Empire District Electric	Hub Opening	Twin Small Closing Plates
Application	Meter Socket With Main And Load Center	Line Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Branch Circuits	8
Amperage Rating	200 Continuous Ampere	Number Of Receptacles	0
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.5L x 14.125W x 30H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.