



MILBANK
ENERGY AT WORK

U5784-O-200-TF



Catalog Number	U5784-O-200-TF	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass 1-200 Ampere Main Pullout 480 Volt Cold Sequence	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572478923	Jaw Quantity	4 Terminal
Length (IN)	4.844	Bypass Type	Lever Bypass
Width (IN)	26	Number of Meter Positions	1 Position
Height (IN)	28	Equipment Ground	Grounding Stud
Brand Name	Milbank	Hub Opening	Plain Top
Type	Ringless Meter Socket	Line Side Wire Range	3/0 AWG - 250 kcmil
Application	Meter Socket With Main	Load Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.844L x 26W x 28H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Fuse Pull Out Switch		
Cable Entry	Underground		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.