



**MILBANK**  
ENERGY AT WORK

## U5785-O-200-TF



Catalog Number	U5785-O-200-TF	Insulation	Glass Polyester
Marketing Product Description	5 Terminal Ringless Plain Top Lever Bypass 1-200 Ampere Main Pullout 480 Volt Cold Sequence 5th Terminal 6 O'clock Position	Mounting	Surface Mount
UPC	784572478947	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	4.844	Jaw Quantity	5 Terminal
Width (IN)	26	Bypass Type	Lever Bypass
Height (IN)	28	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	Grounding Stud
Type	Ringless Meter Socket	Hub Opening	Plain Top
Application	Meter Socket With Main	Line Side Wire Range	3/0 AWG - 250 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	4.844L x 26W x 28H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Fuse Pull Out Switch		
Cable Entry	Underground		
Terminal	Single Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.