



MILBANK
ENERGY AT WORK

U5796-X-400-CB-BL



Catalog Number	U5796-X-400-CB-BL	Insulation	Glass Polyester
Marketing Product Description	7 Terminal Ringless Large Closing Plate Lever Bypass 9-16 In Barrel Lock With Bracket Provision 1-400 Ampere Main Breaker 480 Volt Cold Sequence	Mounting	Surface Mount
UPC	784572479494	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	6.01	Jaw Quantity	7 Terminal
Width (IN)	13	Bypass Type	Lever Bypass
Height (IN)	56	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	2 Barrel Ground Lug
Type	Ringless Meter Socket	Hub Opening	Large Closing Plate
Application	Meter Socket With Main	Line Side Wire Range	Two 3/0 AWG - 500 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Voltage Rating	600 Volts Alternating Current	Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Amperage Rating	320 Continuous Ampere	Number Of Receptacles	0
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	6L x 13W x 56H		
Number Of Cutouts	1		
Cutout Size	One 400 Ampere Main Breaker		
Cable Entry	Overhead		
Terminal	Single Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.