



U5702-O-5T9



| | |
|-------------------------------|---|
| Catalog Number | U5702-O-5T9 |
| Marketing Product Description | 4 Terminal Ringless Plain Top Lever Bypass 2 Main Breaker Provision 5th Terminal 9 O'clock Position Double Pedestal Direct Bury |
| UPC | 784572480018 |
| Length (IN) | 4.13 |
| Width (IN) | 9.875 |
| Height (IN) | 80 |
| Brand Name | Milbank |
| Type | Ringless Meter Socket |
| Application | Mobile Home Power |
| Standard | UL Listed;Type 3R |
| Voltage Rating | Up to 240 Volts Alternating Current |
| Amperage Rating | 200 Continuous Ampere |
| Phase | 1 Phase |
| Frequency Rating | 60 Hertz |
| Size | 4.13L x 9.875W x 80H |
| Number Of Cutouts | 0 |
| Cutout Size | Breaker Provision |
| Cable Entry | Underground |
| Terminal | Double Mechanical |
| Insulation | Glass Polyester |

| | |
|---------------------------|---|
| Mounting | Pedestal |
| Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Jaw Quantity | 5 Terminal |
| Bypass Type | Lever Bypass |
| Number of Meter Positions | Double Power Head |
| Equipment Ground | Ground Bar |
| Hub Opening | Plain Top |
| Number Branch Circuits | 10 |
| Number Of Receptacles | 0 |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.