



**MILBANK**  
ENERGY AT WORK

## U7262-RL-TG-KK-ALT



Catalog Number	U7262-RL-TG-KK-ALT	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Marketing Product Description	4 Terminal Ringless Small Hub Open Triplex Ground Horn Bypass Alliant Energy Narrow Shell	Jaw Quantity	4 Terminal
UPC	784572496293	Bypass Type	Horn Bypass
Length (IN)	4.125	Number of Meter Positions	1 Position
Width (IN)	8	Equipment Ground	Triplex Ground
Height (IN)	15.5	Hub Opening	Small Hub Opening
Brand Name	Milbank	Line Side Wire Range	6 AWG - 350 kcmil
Type	Ringless Meter Socket	Load Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	150 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.125L x 8W x 15.5H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead		
Terminal	Lay in		
Insulation	Glass Polyester		
Mounting	Surface Mount		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.