



**MILBANK**  
ENERGY AT WORK

## UAP5024-XL-FMG



Catalog Number	UAP5024-XL-FMG	Insulation	Glass Polyester
Marketing Product Description	4 Terminal Ringless Small Closing Plate 12 Branch Circuit Aluminum Painted Florida Meter Group	Mounting	Surface Mount
UPC	784572532342	Enclosure	Aluminum with Powder Coat Finish
Length (IN)	4.5	Jaw Quantity	4 Terminal
Width (IN)	14.125	Bypass Type	No Bypass
Height (IN)	24	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	Ground Bar
Type	Ringless Meter Socket	Hub Opening	Small Closing Plate
Special Features	Florida Meter Group	Line Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket With Load Center	Number Branch Circuits	12
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.5L x 14.125W x 24H		
Number Of Cutouts	0		
Cutout Size	Breaker Provision		
Cable Entry	Overhead or Underground		
Terminal	Lay in		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.