



MILBANK
ENERGY AT WORK

U5220-XL-55GBGR



Catalog Number	U5220-XL-55GBGR	Cable Entry	Underground
Marketing Product Description	Unmetered Small Closing Plate 1450GB 520GR Double Pedestal Direct Bury	Terminal	Double Mechanical
UPC	784572639133	Insulation	Glass Polyester
Length (IN)	11.25	Mounting	Pedestal
Width (IN)	8.656	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Height (IN)	64.5	Jaw Quantity	0 Terminals
Brand Name	Milbank	Bypass Type	No Bypass
Type	Unmetered Power Supply	Number of Meter Positions	Double Power Head
Special Features	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Ground Fault Breaker	Equipment Ground	2 Barrel Ground Lug and Ground Bar
Application	RV Power	Hub Opening	Small Closing Plate
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Branch Circuits	6
Amperage Rating	125 Continuous Ampere	Number Of Receptacles	4
Phase	1 Phase	Receptacle Configuration	Two NEMA 14-50 and Two NEMA 5-20 Ground Fault
Frequency Rating	60 Hertz		
Size	11.25L x 8.656W x 64.5H		
Number Of Cutouts	4		
Cutout Size	Two Single Pole 20 Ampere Breakers and Two Double Pole 50 Ampere Ground Fault Breakers		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.