



MILBANK
ENERGY AT WORK

U3849-O-2/200-CECHA



Catalog Number	U3849-O-2/200-CECHA	Cable Entry	Underground
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass 2-200 Ampere Main Breaker Single Pedestal Direct Bury Commonwealth Edison Chicago Housing Authority	Terminal	3/8 Inch Stud
UPC	784572674288	Insulation	Glass Polyester
Length (IN)	4.81	Mounting	Pedestal
Width (IN)	13	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Height (IN)	64	Jaw Quantity	4 Terminal
Brand Name	Milbank	Bypass Type	Lever Bypass
Type	Ringless Meter Socket	Number of Meter Positions	1 Position
Special Features	Commonwealth Edison Chicago Housing Authority	Equipment Ground	2 Barrel Ground Lug
Application	Meter Socket With Main	Hub Opening	Plain Top
Standard	UL Listed;Type 3R	Load Side Wire Range	1 AWG - 300 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	320 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.81L x 13W x 64H		
Number Of Cutouts	2		
Cutout Size	Two 200 Ampere Main Breakers		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.