



MILBANK[®]
ENERGY AT WORK

U5701-O-100S-5T6



| | | | |
|-------------------------------|--|---------------------------|--|
| Catalog Number | U5701-O-100S-5T6 | Insulation | Glass Polyester |
| Marketing Product Description | 5 Terminal Ringless Plain Top Lever Bypass 1-100 Ampere Main Breaker 5th Terminal 6 O'clock Position Single Pedestal Direct Bury | Mounting | Pedestal |
| UPC | 784572674844 | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Length (IN) | 10.27 | Jaw Quantity | 5 Terminal |
| Width (IN) | 9.875 | Bypass Type | Lever Bypass |
| Height (IN) | 80 | Number of Meter Positions | 1 Position |
| Brand Name | Milbank | Equipment Ground | 4 Barrel Ground Lug |
| Type | Ringless Meter Socket | Hub Opening | Plain Top |
| Application | Meter Socket With Main And Load Center | Line Side Wire Range | 6 AWG - 350 kcmil |
| Standard | UL Listed;Type 3R | Load Side Wire Range | 1 AWG - 300 kcmil |
| Voltage Rating | Up to 240 Volts Alternating Current | Number Of Receptacles | 0 |
| Amperage Rating | 200 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 10.27L x 9.875W x 80H | | |
| Number Of Cutouts | 1 | | |
| Cutout Size | One 100 Ampere Main Breaker | | |
| Cable Entry | Underground | | |
| Terminal | Double Mechanical | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.