



MILBANK
ENERGY AT WORK

U6012-XL-200-K1-5T6



Catalog Number	U6012-XL-200-K1-5T6	Terminal	Single Mechanical
Marketing Product Description	5 Terminal Ringless Small Closing Plates Lever Bypass 1-200 Ampere Main Breaker 8 Branch Circuit Single Connector 6-350kcmil 5th Terminal 6 O'clock Position	Insulation	Glass Polyester
UPC	784572676770	Mounting	Surface Mount
Length (IN)	4.5	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	14.125	Jaw Quantity	5 Terminal
Height (IN)	39.25	Bypass Type	Lever Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	Ground Bar
Application	Meter Socket With Main And Load Center	Hub Opening	Small Closing Plate
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Load Side Wire Range	6 AWG - 350 kcmil
Amperage Rating	200 Continuous Ampere	Number Of Receptacles	0
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.5L x 14.125W x 39.25H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.