



U6134-RL-76GBGR



| | |
|-------------------------------|---|
| Catalog Number | U6134-RL-76GBGR |
| Marketing Product Description | 5 Terminal Ringless Small Hub Open Lever Bypass 520GR 520GR 1450GB |
| UPC | 784572696099 |
| Length (IN) | 4.844 |
| Width (IN) | 13 |
| Height (IN) | 35 |
| Brand Name | Milbank |
| Type | Ringless Meter Socket |
| Special Features | Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker |
| Application | Meter Socket |
| Standard | UL Listed;Type 3R |
| Voltage Rating | Up to 240 Volts Alternating Current |
| Amperage Rating | 100 Continuous Ampere |
| Phase | 1 Phase |
| Frequency Rating | 60 Hertz |
| Size | 4.844L x 13W x 35H |
| Number Of Cutouts | 2 |
| Cutout Size | Breaker Provision |
| Cable Entry | Overhead or Underground |

| | |
|---------------------------|---|
| Terminal | Lay in |
| Insulation | Glass Polyester |
| Mounting | Surface Mount |
| Enclosure | Aluminum with Powder Coat Finish |
| Jaw Quantity | 5 Terminal |
| Bypass Type | Lever Bypass |
| Number of Meter Positions | 1 Position |
| Equipment Ground | Ground Bar |
| Hub Opening | Small Hub Opening |
| Line Side Wire Range | 6 AWG - 350 kcmil |
| Load Side Wire Range | 6 AWG - 350 kcmil |
| Number Branch Circuits | 6 |
| Number Of Receptacles | 3 |
| Receptacle Configuration | One NEMA 14-50 and Two NEMA 5-20 Ground Fault |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.