

U5891-X-2/200-K3L-5T6-MLK-AMS



Catalog Number	U5891-X-2/200-K3L-5T6-MLK- AMS
Marketing Product Description	5 Terminal Ringless Large Closing Plate Lever Bypass 2-200 Ampere Main Breaker 12 Branch Circuit Main Lug Kit Single 4-600kcmil Connector Kit Ameren
UPC	784572705098
Length (IN)	6
Width (IN)	29.5
Height (IN)	35
Brand Name	Milbank
Туре	Ringless Meter Socket
Special Features	Ameren Energy
Application	Meter Socket With Main And Load Center
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	320 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	6L x 29.5W x 35H
Number Of Cutouts	2
Cutout Size	Two 200 Ampere Main Breakers

Cable Entry	Overhead or Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	3 Barrel Ground Lug
Equipment Ground Hub Opening	3 Barrel Ground Lug Large Closing Plate
Hub Opening	Large Closing Plate 4 AWG - 600 kcmil or Two 1/0
Hub Opening Line Side Wire Range	Large Closing Plate 4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.