



**MILBANK**  
ENERGY AT WORK

## U1252-RRL-KK-K1-BLG-SLVG



|                               |  |                           |   |
|-------------------------------|--|---------------------------|---|
| Catalog Number                | U1252-RRL-KK-K1-BLG-SLVG   | Insulation                | Glass Polyester   |
| Marketing Product Description | 4 Terminal Ringless Large Hub<br>Open Adapt To Small Hub<br>Open Horn Bypass 2 Position<br>Single Connector 6-350kcmil<br>7-8 In Barrel Lock Ground<br>With Bracket Provision Buss<br>Insulator Sleeve | Mounting                  | Surface Mount   |
| UPC                           | 784572706217   | Enclosure                 | G90 Galvanized Steel with<br>Powder Coat Finish                     |
| Length (IN)                   | 5.125  | Jaw Quantity              | 4 Terminal  |
| Width (IN)                    | 26.5   | Bypass Type               | Horn Bypass   |
| Height (IN)                   | 14   | Number of Meter Positions | 2 Positions   |
| Brand Name                    | Milbank  | Equipment Ground          | Ground Lug  |
| Type                          | Ringless Meter Socket  | Hub Opening               | Large Hub Opening Adapted<br>to Small Hub Opening                   |
| Application                   | Meter Socket   | Line Side Wire Range      | 6 AWG - 350 kcmil   |
| Standard                      | UL Listed;Type 3R  | Load Side Wire Range      | 6 AWG - 350 kcmil   |
| Voltage Rating                | 300 Volts Alternating Current  | Barrel Lock Provision     | 7/8 Inch Knockout and Angle<br>Bracket For Barrel Lock<br>Provision |
| Amperage Rating               | 200 Continuous Ampere  | Number Of Receptacles     | 0   |
| Phase                         | 1 Phase  |                           |   |
| Frequency Rating              | 60 Hertz   |                           |   |
| Size                          | 5.125L x 26.5W x 14H   |                           |   |
| Number Of Cutouts             | 0  |                           |   |
| Cutout Size                   | No Main Breaker  |                           |   |
| Cable Entry                   | Overhead or Underground<br>with Center Wireway   |                           |   |
| Terminal                      | Single Mechanical  |                           |   |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.