



MILBANK
ENERGY AT WORK

U4554-X-Z21-K6SP-LI



Catalog Number	U4554-X-Z21-K6SP-LI	Terminal	Single Mechanical
Marketing Product Description	13 Terminal Ringless Large Closing Plate Test Switch Prewired 21in-41in-10in Painted Steel Single Front Lift Off Cover Hasp Long Island Lighting Company	Insulation	Glass Polyester
UPC	784572720817	Mounting	Surface Mount
Length (IN)	10	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	21	Jaw Quantity	6 Terminal
Height (IN)	41	Bypass Type	No Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	Ground Lug
Special Features	Long Island Lighting Company	Hub Opening	Large Closing Plate
Application	Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Voltage Rating	600 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	320 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	10L x 21W x 41H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.